

MADE IN BRITAIN



Bio-Diesel
Three Phase Specifications



5 Series: 50 – 200kVA

Model Number	kVA	KW	kVA	KW	Engine	Alternator	Fuel Tank Capacity (Litres)
	Prime	Prime	Standby	Standby			
JSPBD50	50	40	55	44	Sisu	Mecc Alte	220
JSPBD60	60	48	66	52.8	Deutz	Mecc Alte	100
JSPBD90	90	72	99	80	Deutz	Mecc Alte	220
JSPBD100	100	80	110	88	Sisu	Mecc Alte	220
JSPBD125	125	100	138	110	Sisu	Mecc Alte	220
JSPBD150	150	120	165	132	Sisu	Mecc Alte	400
JSPBD180	180	144	200	160	Sisu	Mecc Alte	400
JSPBD200	200	160	220	176	Sisu	Mecc Alte	400

Prime: Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period. In accordance with ISO 8528, ISO 3046.

Standby: Continuous running at variable load for duration of an emergency. No overload is permitted on these ratings. In accordance with ISO 3046, BS 5514.

*All specifications subject to change without notice
For detailed technical information - please contact us by telephone or email shown below.

Sales, Service, Refurbishment and Maintenance of Diesel and Biodiesel Generators - UPS Systems



Unit 6, Dairycoates Industrial Estate, Wiltshire Road, Hull. East Riding. HU4 6PA. UK
T: +44 (0) 1482 222565 F: +44 (0) 1482 222646 E: hello@jspower.co.uk W: www.jspower.co.uk
Company Registration: 5047830 VAT Number: 830 0513 80

