

Sales, Service and Maintenance of Diesel | Bio Diesel Generators - UPS Systems





DESIGN SPECIFICATIONS

- ✓ High quality, reliable and complete power unit
- ✓ Compact design
- ✓ Easy start and maintenance
- ✓ Fully tested for load, controls and safety shutdown functions
- ✓ Fully engineered with a range of optional extras and accessories.

400/230v 50 Hz	Generating S	JSP 45	
Power Factor 0.8	Prime	kVA	45
		kW	36
	Standby	kVA	50
		kW	40

Prime: Continuous running at variable load for unlimited periods with 10% overload available for 1 hour in any 12 hour period. In accordance with ISO 8528, ISO 3046. Standby: Continuous running at variable load for duration of an emergency. No overload is permitted on these ratings. In accordance with ISO 3046, BS 5514.

TECHNICAL DATA*						
Engine Model	Perkins 1103A-33TG1	Alternator	Mecc Alte			
Number of Cylinders	3 in-line	Heat Rejection to Exhaust (Max)	35.0 kW			
Cubic Capacity	3.30 litre	Heat Rejection to Cooling System (Max)	30.0 kW			
Aspiration	Turbocharged	Exhaust Temperature (Max)	537 deg C			
Engine Speed (RPM)	1500 rpm	Combustion Air Flow (Max)	3.1 cu m/min			
Frequency	50 Hz	Fuel Tank Capacity	220 litre			
Amperage	65 amp per phase	Fuel Consumption at Full Prime Rating	7.2 litre per hour			

DIMENSIONS*			
Length (A)	2,385 mm		
Width (B)	1,100 mm		
Height including exhaust (C)	1,767 mm		
Max Horizontal projection of end door (D)	1,090 mm		
Max Horizontal projection of side door (E)	1,090 mm		
WEIGHT*			
Wet (with lube oil and coolant)	1,373 kg		

SOUND LEVELS*				
Load	15m	7m	1m	
100%	57.8	63.8	72.5	
75%	57.3	63.3	71.8	



*Picture for illustrative purposes only

FFATUREC*	Manual Start, Main Power Set		Automatic Start, Standby Set	
FEATURES*	Standard	Optional	Standard	Optional
Sound Attenuated, Weatherproof Canopy	✓		✓	
Base Fuel Tank	✓		✓	
DEFRA Bunded Base Fuel Tank (Standard on UK Models)		✓		✓
Oil, Fuel & Air Filters	✓		✓	
Coolant Water Heater			✓	
Lube Oil Drain	✓		✓	
Vibration isolated Control Panel	✓		✓	
Manual Control Panel	✓			
Auto Start Control Panel			✓	
Integral 5A Battery Charger			✓	
Automatic Transfer Panel				✓
12 Months International Warranty	✓		✓	
Output Circuit Breaker	✓		✓	
CE Certification (Standard on UK / EU Models)		✓		✓
Service / Maintenance Contracts/ NetBiter Remote Monitoring		✓		✓





